

Australian/New Zealand Standard™

**Motor vehicles—Cargo barriers for
occupant protection**

Part 1: Cargo barriers



AS/NZS 4034.1:2008

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee ME-084, Cargo Restraint Systems for Occupant Protection in Light Vehicles. It was approved on behalf of the Council of Standards Australia on 18 October 2007 and on behalf of the Council of Standards New Zealand on 29 February 2008.

This Standard was published on 28 March 2008.

The following are represented on Committee ME-084:

Australian Automobile Association
Australian Automotive Aftermarket Association
Australian Industry Group
Department of Transport, Energy and Infrastructure, SA
Department of Labour, New Zealand
Federal Chamber of Automotive Industries
Federation of Automotive Products Manufacturers
Land Transport New Zealand
Society of Automotive Engineers, Australasia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.standards.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

This Standard was issued in draft form for comment as DR 06700.

Australian/New Zealand Standard™

Motor vehicles—Cargo barriers for occupant protection

Part 1: Cargo barriers

Originated as part of AS/NZS 4034:1992.
Previous edition AS/NZS 4034.1:2001.
Third edition AS/NZS 4034.1:2008.

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia, GPO Box 476, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 8595 6

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee ME-048, Cargo Restraint Systems for Occupant Protection in Light Vehicles to supersede AS/NZS 4034.1:2001, *Motor vehicles—Cargo barriers for occupant protection, Part 1: Cargo barriers*.

The objective of this Standard is to provide manufacturers, suppliers and users with the requirements for cargo barriers in order to protect the passengers and drivers, in the event of a collision, when seated in front of cargo in a motor vehicle.

This Standard includes technical, material and testing innovations to cargo barriers. Part 2 of this series of Standards covers the partial cargo barrier to suit hatchback vehicles.

This Standard is Part 1 of AS/NZS 4034, *Motor vehicles—Cargo barriers for occupant protection*, which is published in part as follows:

Part 1: Cargo barriers (this Standard)

Part 2: Partial cargo barriers

The rating system for cargo barriers allows the barriers to be rated in either a test frame or a body shell and quotes alternative methods for impact testing. Whichever test method is chosen, the procedure is based on a single mass of cargo placed against the rear face of the cargo barrier. However, research indicates that during collision cargo barriers of any nominal rating may be capable of restraining cargo comprising of a number of smaller items with a total mass exceeding the nominal rating.

In this revision provision has been made for the use of cargo barriers in vehicles fitted with side airbags. The Committee recognizes that this results in increased clearances in some areas for such vehicles, which increases the risk of objects passing through in the collision, but considers that it is preferable to provide as much protection as possible in these situations rather than no protection at all.

Attention is drawn to labelling information that identifies cargo barriers for use with a side airbag equipped vehicle or with a vehicle not equipped with side airbags.

Child restraint anchorages and associated upper anchorage straps, if located behind the cargo barrier, could be damaged by cargo shifting in the rear of the vehicle during a collision. Attention is drawn to the information to be supplied under Clause 1.7 to overcome this possible problem.

In the 2001 revision, a Clause was added for cargo barrier manufacturers to provide a means for occupants to egress from the vehicle if the vehicle is not equipped with an internal rear compartment door release (refer to Clause 2.3).

The addition of a clause on 'Ageing' of polycarbonate type materials was considered by the Committee, but insufficient evidence was available on the type of materials used within the confines of a motor vehicle. It was agreed that no statement could be made at the stage of publishing.

In preparing this Standard, the German Standard DIN 75410-2, *Securing of cargo in road vehicles, Part 2: Securing of cargo in passenger cars, station wagons and multi-purpose cars* and AS/NZS 4384:1997, *Motor vehicles—Anchorages and anchor points for securing internal cargo* were taken into consideration.

Statements expressed in mandatory terms in footnotes to figures are deemed to be requirements of this Standard.

The term 'normative' has been used in this Standard to define the application of the appendix to which it applies. A 'normative' appendix is an integral part of a Standard.

CONTENTS

	<i>Page</i>
FOREWORD.....	4
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	5
1.2 REFERENCED DOCUMENTS	5
1.3 DEFINITIONS	6
1.4 CONFIGURATIONS	6
1.5 RATING.....	6
1.6 MARKING	9
1.7 PACKAGING.....	12
SECTION 2 DESIGN AND INSTALLATION REQUIREMENTS	
2.1 GENERAL	13
2.2 DEFORMATION	13
2.3 MEANS OF ESCAPE.....	13
2.4 ANCHORAGES	14
2.5 HEAD RESTRAINTS	15
2.6 SEAT BELT CLEARANCE.....	15
2.7 CHILD RESTRAINT DEVICE (CRD) INSTALLATION	15
2.8 ATTACHMENTS.....	15
2.9 CLEARANCE BETWEEN CARGO BARRIER AND VEHICLE	16
2.10 FRAME MEMBERS	16
2.11 HEIGHT ADJUSTMENT IN MULTI-POSITION CARGO BARRIER.....	16
2.12 WINDOW IN CARGO BARRIER	16
2.13 CONSTRUCTION REQUIREMENTS.....	16
2.14 DOOR IN CARGO BARRIER	17
2.15 CARGO BARRIERS FOR VEHICLES FITTED WITH SIDE AIRBAGS.....	17
SECTION 3 PERFORMANCE REQUIREMENTS	
3.1 IMPACT STRENGTH.....	21
3.2 ENERGY LEVEL FOR IMPACT TESTING	21
3.3 PENETRATION	22
3.4 GLARE.....	22
APPENDICES	
A HORIZONTAL TESTS	24
B DROP TEST	30
C PENETRATION TEST.....	39

FOREWORD

The range of performance requirements prescribed in this Standard is intended to decrease the impact hazard in an accident to occupants from cargo carried within the interior of vehicles.

Cargo-related injuries contribute significantly to the total of injuries sustained in traffic accidents. In the past, little attention was paid to the hazard from unrestrained cargo when it intruded into the driver and passenger zone during frontal impacts or when the vehicle overturned.

Accident statistics do not quantify the risk that cargo creates, however, a thorough analysis of accidents, with cargo in the cabin, demonstrates the urgent need for improved cargo retention. Initial crash test program results for vehicles containing unrestrained cargo were of concern because they highlighted the potential for severe injury to occupants and great damage to vehicles.

The cargo barriers specified in this Standard are marked with a rated single mass capacity for cargo positioned against the cargo barrier. The effect of NOT putting the cargo against the rear face of the cargo barrier can increase the impact energy that must be dissipated by a factor of up to five times.

The basis for the performance criteria set by this Standard is the restraint of the nominated capacity of cargo as a single mass during frontal impact of the vehicle as specified in *Australian Design Rules for Motor Vehicles and Trailers*. From the economic viewpoint, it is impractical to verify the performance of the cargo barrier by conducting this type of frontal impact test for motor vehicles. As an alternative, a dropweight test method is specified with equivalent energy dissipation levels.

The single mass rating simulates the most severe condition and if the cargo were to consist of a number of items of smaller mass, a far greater mass of cargo might be restrained by the cargo barrier. However, because of the variety of cargo compositions possible, the Standard does not specify a rating for such conditions. Deceleration levels generated in simulated crash impacts are of the order of 20g.

Two test methods, a drop test and a horizontal test with equivalent energy dissipation, are specified for the demonstration of compliance with the impact strength requirements.

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard
Motor vehicles—Cargo barriers for occupant protection

Part 1: Cargo barriers

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies a range of performance requirements including load ratings for cargo barriers, and their design, installation and usage in vehicles for the protection of occupants.

This Standard does not cover the requirements for other types of dividing devices, such as dog nets, which are not intended specifically to reduce injuries caused by the cargo shifting under crash conditions.

1.2 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

AS	
2700	Colour Standards for general purposes
AS/NZS	
2272	Plywood—Marine
2596	Seat belt assemblies for motor vehicles
4034	Motor vehicles—Cargo barriers for occupant protection
4034.2	Part 2: Partial cargo barriers
4384	Motor vehicles—Anchorages and anchor points for securing internal cargo
SAE	
J850	Fixed Rigid Barrier Collision Tests
ADR*	
4	Seat belts
5	Anchorages for seat belts and child restraints
8	Safety glazing materials
34	Child restraint anchorages and child restraint anchor fittings
69	Full frontal impact occupant protection

* Australian Design Rules for Motor Vehicles and Trailers. This reference refers to the latest edition of the Design Rules.



The remainder of this document
is available for purchase online at

➤ www.saiglobal.com/shop ◀

SAI Global also carries a wide range of publications from a wide variety of Standards Publishers:



Click on the logos to search the database online.